


ATTACCO DI CARICA CON CAPPuccio A DOPPIA GUARNIZIONE - CONNESSIONE FASTLOCK A3-A2L - O.RING IN HNBR
ACCESS FITTING WITH DOUBLE-SEALED CAP - A3-A2L FASTLOCK CONNECTION - HNBR O.RING

ATTACCO DI CARICA CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE OT58 - DADO IN OTTONE OT58 - CONNESSIONE FASTLOCK A3-A2L - O.RING IN HNBR 100% PFAS-FREE CERTIFICATO OLAB - MECCANISMO VALVOLA INTERNO (COD. 31516-B)

ACCESS FITTING WITH DOUBLE-SEALED CAP - OT58 BRASS BODY - OT58 BRASS NUT - A3-A2L FASTLOCK CONNECTION - 100% PFAS-FREE OLAB CERTIFIED HNBR O.RING - INTERNAL VALVE MECHANISM (CODE 31516-B)



CARATTERISTICHE

PS : 52 bar
TS : -40°C ÷ +150°C

- Corpo in ottone CW614N OT58
- Componenti in ottone CW614N OT58
- Bussola di rinforzo anti-sfilamento del tubo in acciaio inox
- O.Ring in HNBR 100% PFAS-FREE certificato OLAB
- Doppio O.Ring in ogni possibile punto di perdita
- Connessione FASTLOCK A3-A2L brevettata
- Disponibile anche con sigillo di piombatura
- Cappuccio con sede conica (45°)

VANTAGGI

- Nessuna saldatura né perdita grazie alla connessione FASTLOCK
- Tenuta garantita da due guarnizioni, una superiore ed una inferiore
- La forma esagonale del cappuccio garantisce la chiusura dell'attacco di carica mediante una semplice chiave, dando così modo all'operatore di potere ricaricare l'impianto e di risigillarlo perfettamente senza nessun tipo di perdita grazie alla doppia guarnizione.
- Collaudate al 100% con modernissimo impianto ad elio 100%
- Dati di collaudo impressi per permettere la rintracciabilità

HNBR 100% PFAS-FREE compound specifico per utilizzo con gas refrigerante A3-A2L



L'unico attacco di carica con cappuccio a doppia guarnizione

GENERAL FEATURES

PS: 754 psi
TS: -40°F ÷ 302°F

- CW614N OT58 brass body
- CW614N OT58 brass components
- Stainless steel tube anti-slip reinforcement bushing
- 100% PFAS-FREE OLAB certified HNBR O.Ring
- Double O.ring at every possible leakage point
- Patented A3-A2L FASTLOCK connection
- Also available with lead seal
- Cap with conical seat (45°)

ADVANTAGES

- No welding, no leakage: thanks to the FASTLOCK connection
- Sealing guaranteed by two gaskets, one upper and one lower
- The hexagonal shape of the cap guarantees the closing of the charging connection by means of a simple key, thus allowing the operator to be able to recharge the system and to reseal it perfectly without any kind of leak thanks to the double gasket
- 100% tested with modern 100% helium plant
- Test data marked to ensure traceability

100% PFAS-FREE HNBR specific compound for use with A3-A2L refrigerant gas

The only access fitting with a cap with double sealing gasket

SAFELOCK

100%

PATENT PENDING

SAFELOCK

THE MOST ADVANCE A3-A2L ACCESS FITTING

La Serie K10042 per A1, A2L e A3, unisce il miglior attacco di carica alla connessione Fast Lock, garantendo affidabilità e sicurezza fino a 52 bar (754 psi). Dotata di cappuccio con doppia guarnizione in HNBR certificato OLAB 100% PFAS-FREE e sistema Fast Lock, elimina la necessità di saldature, assicurando una tenuta perfetta grazie alla bussola di rinforzo brevettata con gola anti-sfilamento (AST).


The Series K10042 for A1, A2L, and A3 combines the best access fitting with the Fast Lock connection, ensuring reliability and safety up to 52 bar (754 psi). Equipped with a cap featuring double O.R.s in OLAB-certified 100% PFAS-FREE HNBR and the Fast Lock system, it eliminates the need for welding, providing a perfect seal thanks to the reinforcement bush with patented anti-slip tube groove (AST).

MONTAGGIO FACILE
EASY ASSEMBLY




TAGLIA & PULISCI
CUT & CLEAN

1




INSERISCI
INSERT

2



ASSEMBLA
ASSEMBLE

3



CHIUDI
CLOSE

4

A3-A2L FAST LOCK ACCESS FITTING



SO SIMPLE **ANYONE CAN DO IT**

100% EASY TO INSTALL
FITS TIGHT SPACES

SIMPLEFIT

100%

NO SPECIALIZED PERSONNEL REQUIRED



PFAS
FREE


EXCLUSIVE **O-RING COMPOUND**

100% TAILOR MADE
PERFECT SEAL

OLAB **HNBR**

100%

OLAB CERTIFIED COMPOUND




THE PERFECT **SEAL SYSTEM**

100% TOTAL SECURITY
NO LEAKAGE

FAST LOCK

100%

OLAB CERTIFIED HNBR



DOUBLE O-RING ACCESS FITTING

100% SAFE SEALING
NO LEAKAGE

SAFE CAP

100%

OLAB CERTIFIED HNBR

ATTACCO DI CARICA CON CAPPuccio A DOPPIA GUARNIZIONE - CONNESSIONE FASTLOCK A3-A2L - O.RING IN HNBR
ACCESS FITTING WITH DOUBLE-SEALED CAP - A3-A2L FASTLOCK CONNECTION - HNBR O.RING

PS : 52 bar PS: 754 psi
TS : -40°C ÷ +150°C TS: -40°F ÷ 302°F

ATTACCO DI CARICA CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE OT58 - DADO IN OTTONE OT58 - CONNESSIONE FASTLOCK A3-A2L - O.RING IN HNBR 100% PFAS-FREE CERTIFICATO OLAB - MECCANISMO VALVOLA INTERNO (COD. 31516-B)

ACCESS FITTING WITH DOUBLE-SEALED CAP - OT58 BRASS BODY - OT58 BRASS NUT - A3-A2L FASTLOCK CONNECTION - 100% PFAS-FREE OLAB CERTIFIED HNBR O.RING - INTERNAL VALVE MECHANISM (CODE 31516-B)



Codice Code	F.M. SAE M.T. SAE	Øin	Ømm	Orifizio Orifice (mm)	Conf. Pack.	Lotto min. Min. lot
K10042-01B-01-G	1/4"	1/4"x0,8		2,4	500	
K10042-M06A-01-G	1/4"		6x1	2,4	500	

MECCANISMO VALVOLA CON MOLLA ESTERNA E GUARNIZIONI IN HNBR 100% PFAS-FREE CERTIFICATO OLAB
TEMPERATURA DI UTILIZZO: -25° : +130°C

VALVE MECHANISM WITH EXTERNAL SPRING AND 100% PFAS-FREE OLAB CERTIFIED HNBR GASKET
TEMPERATURE OF USE : -13° : +266°F



Codice Code	Guarnizione Gasket	Pressione di utilizzo Operating pressure (bar)	PS max (bar)	Conf. Pack.	Lotto min. Min. lot
31516-B	HNBR	0÷60	200	1000	1000

