

ATTACCO DI CARICA BREVETTATO CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE
PATENTED ACCESS FITTING WITH DOUBLE O.RING CAP - BRASS BODY

ATTACCO DI CARICA BREVETTATO CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE - O.RING IN EPDM 100% PFAS-FREE
CERTIFICATO OLAB

PATENTED ACCESS FITTING WITH DOUBLE O.RING CAP - BRASS BODY - 100% PFAS-FREE OLAB CERTIFIED EPDM O.RING



CARATTERISTICHE

PS : 120 bar
TS : -50°C ÷ +150°C

- Attacco di carica brevettato OLAB con cappuccio a doppia guarnizione
- Corpo in ottone giallo
- Doppio O.Ring in EPDM certificato OLAB 100% PFAS-FREE
- Cappuccio con sede conica (45°)

VANTAGGI

- Tenuta sicura: garantita dalla doppia guarnizione, una superiore ed una inferiore
- Attacco di carica facile da montare
- Collaudato al 100%: con modernissimo impianto ad elio 100% Su ognuno di essi vengono impressi la data e il n. seriale che ne attesta il superamento del collaudo e permette la rintracciabilità nel tempo dei dati di prestazione registrati durante il test

EPDM 100% PFAS-FREE compound specifico per utilizzo con gas refrigerante R744 (CO₂)

GENERAL FEATURES

PS: 1740 psi
TS: -58°F ÷ 302°F

- OLAB patented access fittings with double O. Ring cap
- Yellow brass body
- Double OLAB certified 100% PFAS-FREE EPDM O.Ring
- Cap with conical seat (45°)

ADVANTAGES

- Safe sealing: guaranteed by double gasket, one upper and one lower
- Easy-assembly charging connection
- 100% tested: with modern 100% helium plant, each cap bears the date and serial number proving that it has passed the test and allowing traceability of the performance data measured during testing over time


100% PFAS-FREE EPDM specific compound for use with R744 (CO₂) refrigerant gas

ATTACCO DI CARICA BREVETTATO CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE
PATENTED ACCESS FITTING WITH DOUBLE O.RING CAP - BRASS BODY

PS: 120 bar PS: 1740 psi
TS: -50 °C ÷ +150 °C TS: -58°F ÷ +302°F

CAPPuccio CON FILETTO FEMMINA - DOPPIO O.RING IN EPDM 100% PFAS-FREE CERTIFICATO OLAB

CAP WITH FEMALE THREAD - 100% PFAS-FREE OLAB CERTIFIED EPDM O.RING

 F.F.		 			
		Codice Code	Attacchi - Connections	Conf. Pack.	Lotto min. Min. lot
		XK09323-C	F.F. SAE 1/4"	500	2000

CORPO ATTACCO DI CARICA DRITTO CON FILETTO MASCHIO SAE E TUBO SALDATO - DEDICATO AL CAPPuccio XK09323-C

STRAIGHT SERVICE PORT ADAPTER BODY WITH SAE MALE THREAD AND WELDED PIPE - DEDICATED TO XK09323-C CAP



F.M.

L









Attacchi - Connections					
Codice Code	F.M.	Ø T	Conf. Pack.	Lotto min. Min. lot	
K09332	SAE 1/4"	6x1 - L: 60	1000	2000	
K09332-A	SAE 1/4"	6x1 - L: 90	1000	2000	

ATTACCO DI CARICA BREVETTATO CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE
PATENTED ACCESS FITTING WITH DOUBLE O.RING CAP - BRASS BODY

PS: 120 bar PS: 1740 psi
TS: -50 °C ÷ +150 °C TS: -58°F ÷ +302°F

ATTACCO DI CARICA IN OTTONE MASCHIO GAS CILINDRICO CON O.RING IN EPDM 100% PFAS-FREE CERTIFICATO OLAB - FILETTO MASCHIO 1/4" SAE DEDICATO AL CAPPuccio SERIE XK09323-C

BRASS MALE CYLINDRICAL GAS SERVICE PORT WITH 100% PFAS-FREE OLAB CERTIFIED EPDM O.RING - 1/4" MALE SAE THREAD DEDICATED TO SERIES XK09323-C CAP



Codice Code	Attacchi - Connections		Conf. Pack.	Lotto min. Min. lot
	F.M. 1	F.M. 2		
31518-01-01-LP	1/4"G	1/4"SAE		250
31518-01-02-LP	3/8"G	1/4"SAE		250

CORPO ATTACCO DI CARICA DRITTO CON FILETTO MASCHIO SAE E TASCA A SALDARE - DEDICATO AL CAPPuccio XK09323-C

STRAIGHT SERVICE PORT ADAPTER BODY WITH SAE MALE THREAD AND WELDING SOCKET - DEDICATED TO XK09323-C CAP



Codice Code	Attacchi - Connections		Conf. Pack.	Lotto min. Min. lot
	F.M.	S.W.		
CK09323-100-G	SAE 1/4"	6	500	2000
CK09323-101-G	SAE 1/4"	1/4"	500	2000

ATTACCO DI CARICA BREVETTATO CON CAPPuccio A DOPPIA GUARNIZIONE - CORPO IN OTTONE
PATENTED ACCESS FITTING WITH DOUBLE O.RING CAP - BRASS BODY

PS: 140 bar PS: 2030 psi
TS: -50 °C ÷ +150 °C TS: -58°F ÷ +302°F

MECCANISMO VALVOLA CON MOLLA ESTERNA - O.RING IN EPDM 100% PFAS-FREE CERTIFICATO OLAB

VALVE MECHANISM WITH EXTERNAL SPRING - 100% PFAS-FREE OLAB CERTIFIED EPDM O.RING



Codice Code	Pressione di utilizzo Operating pressure (bar)	Conf. Pack.	Lotto min. Min. lot
31516-C	0÷60 / 0÷870	1000	1000

